

Material - DIN NiCr21Mo

Standard Specification for Strips and Sheets of Nickel and Nickel Alloys

Group - Non-Ferrous Nickel Alloys

Sub Group - DIN NiCr21Mo Strips and Sheets of Nickel and Nickel Alloys

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Strip and Sheet

Chemical Composition			Heat Treatment	
Carbon	C %	0.025 max.		
Silicon	Si %	0.500 max.		
Manganese	Mn %	1.000 max.	As-Cast or Annealing or Age Hardning	
Chromium	Cr %	19.500 - 23.500		
Copper	Cu %	1.500 - 3.000		
Cobalt	Co %	1.000 max.		
Aluminium	Al %	0.200 max.		
Molybdenum	Mo %	2.500 - 3.500		
Phosphorus	P %	0.020 max.	Mechanical Properties	
Sulphur	S %	0.010 max.	Tensile Strength in Mpa	500 min.
Titanium	Ti %	0.600 - 1.200	Yield Strength in Mpa	220 min.
Nickel	Ni %	38.000 - 46.000	Elongation in %	20 min.
Iron	Fe %	Balance	Reduction of Area in %	-
-	-	-	Hardn <mark>ess in H</mark> B	210 max.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
2.4858	DIN	Germany	Strip and Sheet	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS