



Material - Gravity MP35N

Standard Specification for Cobalt-Based alloy, Sheet

Group - Non-Ferrous Cobalt Alloys

Sub Group - Gravity MP35NCobalt-Based alloy, Sheet

Application - Intended for Valve, Pump, General Engineering, Automotive, Medical and other Industries Grade Belongs to the Industry - Sheet

Chemical Composition			Heat Treatment	
Carbon	C %	0.025 max.	As-Cast or Annealing	
Chromium	Cr %	19.000 - 21.000		
Molybdenum	Mo %	9.000 - 10.500		
Nickel	Ni %	33.000 - 37.000		
Iron	Fe %	1.000 max.		
Silicon	Si %	0.150 max.		
Manganese	Mn %	0.150 max.		
Phosphorus	P %	0.015 max.		
Sulphur	S %	0.010 max.	Mechanical Properties	
Titanium	Ti %	1.000 max.	Tensile Strength in Mpa	792 - 2200
Boron	В %	0.015 max.	Yield Strength in Mpa	276 - 1861
Cobalt	Co %	Balance	Elongation in %	`3 - 70
-	-	-	Reduction of Area in %	70 min.
-	-	-	Hardness in HRB	43 min.
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
F688 R30035	ASTM	USA	Plate and Sheet	
-	-	·	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.