



## Material - IS 10569 CuAl7Fe3Sn

## Standard Specification for Aluminium Bronze Rods, Bars and Sections

**Group - Non-Ferrous Copper Alloy** 

Sub Group - IS 10569 Aluminium Bronze Rods, Bars and Sections

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Rod, Bar and Section

Chemical Composition			Heat Treatment	
Lead	Pb %	0.050 max.		
Tin	Sn %	0.200 - 0.500		
Silicon	Si %	0.100 max.		
Nickel	Ni %	0.250 max.	As Raw or Annealing	
Magnesium	Mg %	0.050 max.		
Zinc	Zn %	0.100 max.		
Manganese	Mn %	0.250 max.		
Iron	Fe %	2.000 - 3.000		-
Aluminium	Al %	6.000 - 7.500	Mechanical Properties	
Other	Ot%	0.250 max.	Tensile Strength in Mpa	540 min.
Copper	Cu %	Balance	Yield Strength in Mpa	240 min.
-	-	-	Elongation in %	25 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table					
Material	Standard	Country	Grade Belong to the Industry		
-	-	-	-		
-	-	·	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.