

Material - IS 2378 Cu CATH

Standard Specification for Code for Designation of Copper and Copper Alloys

Group - Non-Ferrous Copper Alloy

Sub Group - IS 2378 Code for Designation of Copper and Copper Alloys

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Casting, Rod and Bar

Chemical Composition			Heat Treatment	
Bismuth	Bi %	0.001 max.		
Lead	Pb %	0.005 max.		
Other	Ot%	0.030 max.		
Copper	Cu %	99.90 max.	As Raw	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	-
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	-
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
Cu ETP	IS	India	Ingot and Casting	
CuCATH-2	IS	India	Ingot and Casting	
-	-	-	-	
-	-	-		
-	-	-	-	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS