

Material - IS 304 Grade HTB 2

Standard Specification for High Tensile Brass Ingots and Castings

Group - Non-Ferrous Copper Alloy

Sub Group - IS 304 High Tensile Brass Ingots and Castings

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade Belongs to the Industry - Ingot and Casting

Chemical Composition			Heat Treatment	
Lead	Pb %	0.200 max.		
Tin	Sn %	0.200 max.		
Silicon	Si %	0.100 max.	As-Cast	
Iron	Fe %	1.500 - 3.250		
Aluminium	Al %	3.000 - 6.000		
Manganese	Mn %	4.000 max.		
Other	Ot%	0.200 max.		
Cu + Ni	Cu%+Ni%	55.000 min		
Zinc	Zn %	Balance	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	740 min.
-	-	-	Yield Strength in Mpa	-
-	-	-	Elongation in %	11 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS