

Material - ISO 121 Mg-Al9Zn

Standard Specification for Magnesium-Aluminium-Zinc Alloy Casting

Group - Non-Ferrous Magnesium-Aluminium-Zinc Alloy

Sub Group - ISO 121 Magnesium-Aluminium-Zinc Alloy Casting

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Bar and Wire

Chemical Composition			Heat Treatment	
Zinc	Zn %	0.200 - 1.000		
Manganese	Mn %	0.150 - 0.600		
Silicon	Si %	0.300 max.		
Iron	Fe %	0.050 max.	As-Cast or Solution Treated or Fully Treated	ed or Fully Treated
Copper	Cu %	0.200 max.		
Nickel	Ni %	0.010 max.		
Aluminium	Al %	8.300 - 10.300		
Magnesium	Mg %	Balance		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	140 min.
-	-	-	Yield Strength in Mpa	75 min.
-	-	-	Elongation in %	1 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardn <mark>ess in BH</mark> N	-
-	-	-	Impac <mark>t in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
MgAl9Zn Class 3	JIS	Japan	Casting	
EN-MC21121	ONORM	Australia	Ingot and Casting	
EN-MC21121	DIN	Germany	Ingot and Casting	
EN-MC21121	UNI	Italy	Ingot and Casting	
EN-MC21121	CSN	Czech Republic	Ingot and Casting	
EN-MC21121	MSZ	Hungary	Ingot and Casting	
EN-MC21121	PN	Poland	Ingot and Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS