



Material - ISO 3522 Al Cu4MgTi

Standard Specification for Aluminium and Aluminium Alloys

Group - Non-Ferrous Aluminium Alloy

Sub Group - ISO 3522 for Aluminium and Aluminium Alloys

Application - Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Silicon	Si %	0.200 max.		
Iron	Fe %	0.350 max.		
Copper	Cu %	4.200 - 5.000		
Manganese	Mn %	0.100 max.	As-Cast,or Solution Anneling and Aging	
Magnesium	Mg %	0.150 - 0.350		
Nickel	Ni %	0.050 max.		
Zinc	Zn %	0.100 max.		
Lead	Pb %	0.050 max.		
Tin	Sn %	0.050 max.	Mechanical Properties	
Titanium	Ti %	0.150 max.	Tensile Strength in Mpa	300 min.
Other	Ot%	0.100 max.	Yield Strength in Mpa	200 min.
Aluminium	Al %	Balance	Elongation in %	5 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in HBW	90 min.
-	-		Impact in Joule	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
EN AC-21000	ASME	USA	Casting	
EN AC-21000	DIN	Germany	Casting	
EN AC-21000	UNE	Spain	Casting	
EN AC-21000	SFS	Finland	Casting	
EN AC-21000	MSZ	Hungary	Casting	
EN AC-21000	AFNOR NF	France	Casting	
EN AC-21000	BDS	Bulgaria	Casting	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.