

## Material - NMX CW-12M

Standard Specification for Castings, Iron-Chromium, Iron-Choromium-Nickel Corrosion Resistant, for General Application

**Group - Non-Ferrous Nickel Alloys** 

Sub Group - NMX CW-12M Castings, Iron-Chromium, Iron-Choromium-Nickel Corrosion Resistant, for General Application

Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Casting

Chemical Composition			Heat Treatment	
Carbon	C %	0.120 max.		
Silicon	Si %	1.500 max.		
Manganese	Mn %	1.000 max.		
Chromium	Cr %	15.500 - 20.000	As-Cast or Annealing or Age Hardning	
Iron	Fe %	7.500 max.		
Molybdenum	Mo %	16.000 - 20.000	-	
Phosphorus	Р%	0.040 max.		
Sulphur	S %	0.030 max.		
Cobalt	Co %	2.500 max.	Mechanical Properties	
Vanadium	V %	0.400 max.	Tensile Strength in Mpa	495 min.
Tungsten	W %	5.250 max.	Yield Strength in Mpa	315 min.
Nickel	Ni %	Balance	Elongation in %	4 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impac <mark>t in Joule</mark>	-
		-		

Cross Reference Table				
Material	Standard	Country Grade Belong to the Industry		
10774 Grade 13	IS	India	Casting	
A 743 Grade CW-12M	ASTM	USA	Casting	
-	-	1	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	
-	-	-	-	

## Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

## ONE STOP SOLUTION FOR METAL PARTS