



Material - SAE Inconel 600

Standard Specification for Nickel Alloy, Corrosion and Heat Resistant, Bars, Forgings and Rings

Group - Non-Ferrous Nickel Alloys

Sub Group - SAE Inconel 600 Nickel Alloy, Corrosion and Heat Resistant, Bars, Forgings and Rings Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries Grade Belongs to the Industry - Pipe Flange, Fitting and Valve

Chemical Composition			Heat Treatment	
Carbon	C %	0.150 max.		
Silicon	Si %	0.500 max.		
Manganese	Mn %	1.000 max.		
Chromium	Cr %	14.000 - 17.000	As-Cast or Annealing or Age Hardning	or Age Hardning
Copper	Cu %	0.500 max.		
Sulphur	S %	0.015 max.		
Iron	Fe %	6.000 - 10.000		
Aluminium	Al %	0.350 max.		
Cobalt	Co %	1.000 max.	Mechanical Properties	
Niobium	Nb %	1.000 max.	Tensile Strength in Mpa	517 - 1276
Titanium	Ti %	0.500 max.	Yield Strength in Mpa	172 - 1207
Phosphorus	P %	0.040 min.	Elongation in %	2 - 50
Tantalum	Ta %	0.050 max.	Reduction of Area in %	40 - 70
Nickel	Ni %	72.000 min.	Hardness in HRC	65 min.
-	-	-	Impa <mark>ct in Joule</mark>	-

Cross Reference Table				
Material	Standard	Country	Grade Belong to the Industry	
HARPER 600	SAE	USA	Pipe Flange, Fitting and Valve	
N06600	UNS	USA	Pipe Flange, Fitting and Valve	
NIREX	SAE	USA	Pipe Flange, Fitting and Valve	
PYROMET 600	SAE	USA	Pipe Flange, Fitting and Valve	
SIMALLOY 600	SAE	USA	Pipe Flange, Fitting and Valve	
-	-	-	-	
-	-	-	-	

Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email marketing@gravitycastindia.com

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

ONE STOP SOLUTION FOR METAL PARTS