



**GRAVITY CAST PVT. LTD.**  
**GRAVITY GROUP OF COMPANIES**

## Material - SAE SIMALLOY

**Standard Specification for Nickel Alloy, Corrosion and Heat-Resistant, Wire**

**Group - Non-Ferrous Nickel Alloys**

**Sub Group - SAE SIMALLOY Nickel Alloy, Corrosion and Heat-Resistant, Wire**

**Application - Intended for Valve, Pump, General Engineering, Automotive and other Industries**

**Grade Belongs to the Industry - Wire**

| Chemical Composition |           |             | Heat Treatment   |  |
|----------------------|-----------|-------------|--|--|
| Carbon               | C %       | 0.080 max.  | As-Cast or Annealing or Age Hardning   |  |
| Silicon              | Si %      | 0.500 max.  |  |  |
| Manganese            | Mn %      | 1.000 max.  |  |  |
| Chromium             | Cr %      | 15.500 max. |  |  |
| Aluminium            | Al %      | 0.700 max.  |  |  |
| Copper               | Cu %      | 0.500 max.  |  |  |
| Ca + Ta              | Ca% + Ta% | 0.900 max.  |  |  |
| Titanium             | Ti %      | 2.500 max.  |  |  |
| Iron                 | Fe %      | 8.000 max.  |  |  |
| Ni + Co              | Ni% + Co% | 73.000 min. |  |  |
| -                    | -         | -           | <b>Mechanical Properties</b><br>Tensile Strength in Mpa      759 - 1897<br>Yield Strength in Mpa      345 - 1656<br>Elongation in %      2 - 45<br>Reduction of Area in %      30 - 60<br>Hardness in HRC      93 min.<br>Impact in Joule      - |  |
| -                    | -         | -           |  |  |
| -                    | -         | -           |  |  |
| -                    | -         | -           |  |  |
| -                    | -         | -           |  |  |
| -                    | -         | -           |  |  |
| -                    | -         | -           |  |  |

| Cross Reference Table |          |         |                              |
|-----------------------|----------|---------|------------------------------|
| Material              | Standard | Country | Grade Belong to the Industry |
| Inconel X750          | SAE      | USA     | Wire                         |
| N07750                | UNS      | USA     | Wire                         |
| UNITEMP 750           | SAE      | USA     | Wire                         |
| -                     | -        | -       | -                            |
| -                     | -        | -       | -                            |
| -                     | -        | -       | -                            |
| -                     | -        | -       | -                            |

**Further any inquiry to discuss with Gravity Cast Pvt. Ltd. – Gravity Group of Companies team member Call on +918469160029, or email [marketing@gravitycastindia.com](mailto:marketing@gravitycastindia.com)**

All information in our data sheets and website is indicative only and is not intended to be a substitute for the full specification from which it is extracted. It is intended to provide typical values to allow comparison between metal alloy option rather than a definitive statement of mechanical performance or suitability for a particular application as these will vary with temperature, product type and product application. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of business.

**ONE STOP SOLUTION FOR METAL PARTS**